

Features	Test Method	Value
Water Absorption	ANSI / ISO - %	10% ≤ E ≤ 18% - P4
Abrasion Resistance	ANSI / ISO	Class 0
Scratch Hardness (MOHS)	ANSI / ISO	Matte - 2 Glossy - 2
Breaking Strength	ANSI / ISO	> 230 lbf > 1000 N
Slip Resistance	ANSI - DCOR (WET) ISO - R VALUE	N/A
Chemical Resistance	ANSI / ISO	Class B
Stain Resistance	ANSI ISO	Class B Class 4
Frost Resistance	ANSI / ISO	Not Resistant
		This product is GREENGUARD® certified.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Ceramic Wall Tile
- Matte | Glossy Finishes
- 7mm | 8mm | 9mm Thicknesses
- Pressed Edge
- V1 - Uniform Variation
- Frost Resistance = No

Features	Test Method	Value	
		Mosaics	Pattern Mosaics
Water Absorption	ANSI / ISO - %	≤ 0.5	< 0.5
Abrasion Resistance	ANSI / ISO	Class 0, 3, 4	Class 4
Scratch Hardness (MOHS)	ANSI / ISO	Glossy - 5 Matte - 6 Unglazed - 7	Matte - 6
Slip Resistance	ANSI - DCOF (WET) ISO - R VALUE	Glossy: < 0.42 / R(-) Matte: < 0.42 / R (-) Unglazed: > 0.65 / R10	Matte: < 0.42 / R(-)
Breaking Strength	ANSI / ISO	> 275 lbf > 1220 N	
Chemical Resistance	ANSI / ISO	Class A	
Stain Resistance	ANSI ISO	Class A Class 5	
Frost Resistance	ANSI / ISO	Resistant	
		This product is GREENGUARD® certified	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed | Through Body Porcelain Mosaics
- Matte | Glossy Finishes
- 6mm Thickness
- Pressed Edge
- PEI Rating = 3 (Glazed Matte) | 4 (Unglazed Matte and Pattern Mosaic)
- V1 - Uniform Variation
- Frost Resistance = Yes

