

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.6% / ± 2mm
Thickness		± 5% / ± 0.5mm
Straightness of Sides		± 0.5% / ± 1.5mm
Rectangularity		± 0.5% / ± 2mm
Surface Flatness		± 0.5% / ± 2mm
Water Absorption	ISO 10545-3	≤ 0.5%
Bending Strength	ISO 10545-4	35 N/mm ² min.
Breaking Strength		1300 N min.
Abrasion Resistance	ISO 10545-6	175 mm ³ max.
Frost Resistance	ISO 10545-12	Required
Chemical Resistance	ISO 10545-13	min. UB
Dynamic Coefficient of Friction (DCOF)	ANSI A137.1	Matte/Grip - WET: > 0.42
Recycled Content	-	> 30%

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Through Body Porcelain Tile
- Matte | Half Polished | Grip Finish
- 9mm | 10mm Thickness
- Rectified Edge
- PEI Rating = 5
- V3 - Moderate Variation
- Frost Resistance = Yes

