

Features	Test Method	Value
Thickness	EN ISO 10545 - 2	± 2.5%
Length / Width		≤ ± 0.25%
Straightness of Side		± 0.15%
Rectangularity		± 0.4%
Surface Flatness		± 0.3%
Water Absorption	EN ISO 10545 - 3	15% to 17%
Weight / M <sup>2</sup>	-	16.00 kg
Modulus of Rupture	EN ISO 10545 - 4	≥ 25N / mm <sup>2</sup>
Thermal Shock	EN ISO 10545 - 9	Pass
Frost Resistance	EN ISO 10545 - 12	Not Suitable
Chemical Resistance	EN ISO 10545 - 13	Class A - B
Stain Resistance	EN ISO 10545 - 14	Class 3
Fire Rating	-	Class A1 / Non Combustible
Recycled Content	-	Up to 20%

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.


**Product Info:**

- Ceramic Tile
- Gloss Finish
- 8mm Thickness
- V3 - Moderate Variation
- Frost Resistance = No


[www.genrose.com](http://www.genrose.com)