

Features	Test Method	Value
Water Absorption	ASTM C373	≤ 0.5%
Thickness	ASTM C499	max ± 0.030 inch
Scratch Hardness	-	7 MOHS
Breaking Strength	ASTM C648	≥ 456 lbf. avg.
Bond Strength	ASTM C482	≥ 50 PSI (0.34 MPa)
Thermal Shock Resistance	ASTM C484	Resistant
Frost Resistance	ASTM C1378	Resistant
DCOF (WET)	ANSI A326.3	≥ 0.42
Recycled Material	-	40%
	This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.	
	This product has a permanent Microban treatment on the surface to reduce the growth of mold, mildew, and bacteria. The antimicrobial technologies from Microban do not need to be reapplied or activated and are registered with the Environmental Protection Agency (EPA) in the US and comply with the standards of the Biocidal Products Regulation (BPR) in Europe.	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Each 7x7 Hex Mosaic is (waterjet-cut) sold (6) pieces to a carton in a mixed assortment of A,B and C layouts. Total coverage per carton is 5.12 SQ.FT.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 10mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes

Intended Uses:

- Residential
- Light Commercial
- Heavy Commercial



www.genrose.com