

Features	Test Method	Value		
		Soft Matte	Structured	
Size	ISO 10545-2	Conforms		
Water Absorption	ISO 10545-3	≤ 0.1%		
Bending Strength	ISO 10545-4	Conforms		N/A
Breaking Strength		Sps ≥ 7.5 mm S ≥ 1300 N	> 10,000 N	
Deep Scratch Resistance	ISO 10545-6	Conforms		
Thermal Linear Expansion Coefficient	ISO 10545-8	~ 7 (10 ⁻⁶ °C ⁻¹)		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Expansion in Humidity	ISO 10545-10	≤ 0.1 (mm/m)		
Frost Resistance	ISO 10545-12	Resistant		
Resistance to Chemical Attack	ISO 10545-13	Resistant	Cleanable	
Resistance to Stains	ISO 10545-14	Cleanable		
Static Load	EN 12825	-	KN > 7.0 KN > 5.0 KN > 8.0	
Breaking Load Class	EN 1339	-	U11 T11	
Slip Resistance	DIN 51130 - DIN 51097	R9 Matte 48" x 110"	R10 B Matte - Soft	R11 C
	DCOF	0.43		0.74
Recycled Content	-	20% Excludes Candle, Glare and Decos		
Sustainability / Conformance	This product will contribute to USGBC registered LEED projects. It also conforms with ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material - Zero VOC			

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Wall Deco Installation Instructions: When laying the material it is recommended not to use mechanical leveling systems, which could cause damage to the surface when removed. Before grouting wall decos, it is advised to protect the surface in the parts near the edge with masking tape. Cement-based, not epoxy-based, grouts must be used. Immediately after grouting, remove any residues with water and a soft cloth, without using abrasive sponges.

Cleaning and Maintenance Wall Decos: For ordinary cleaning, avoid abrasive products that could damage the surface. Cleaning with a soft cloth and neutral PH products is recommended to avoid dulling or scratching.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Rectified Edge
- Matte | Soft | Structured Finishes
- V2 - Slight Shading Variation
- 6mm | 9mm | 20mm Thicknesses
- Frost Resistance = Yes



www.genrose.com