

Features	Test Method	Value		
Dimensions	ISO 10545 - 2	Compliant		
Surface Quality		Min. 95% of tiles free of visible defects		
Water Absorption	ISO 10545 - 3	≤ 0.1%		
Bending Strength	ISO 10545 - 4	Soft Matte	Anti-Slip	
		58.8 N/mm³	≥ 3,000 N	
Breaking Strength		S ≥ 1300 N	> 10,000 N	
Deep Abrasion Resistance	ISO 10545 - 6	142mm³		
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	≥ 7 (10 ⁻⁶ °C ⁻¹)		
Thermal Shock Resistance	ISO 10545 - 9	Resistant		
Crazing Resistance	ISO 10545 - 11	Resistant		
Chemical Resistance (Domestic)	ISO 10545 - 13	A		
Chemical Resistance (Low Concentration)		LA		
Chemical Resistance (High Concentration)		HA		
Slip Resistance (Wet)	ANSI A326.3	Soft	Matte	Anti-Slip
		DCOF 0.43	DCOF 0.74	DCOF 0.80
Fire Resistance	-	A1/A1 _{FL}		
LEED	-	Yes		
Recycled Content	-	20% *Excludes Candle, Glare and Decos		
VOC Emissions	-	Zero VOC		
Environmental Product Declaration	-	Product-Specific		
Health Product Declaration	-	Available		
Declare	-	Red List Free		



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Wall Deco Installation Instructions: When laying the material it is recommended not to use mechanical leveling systems, which could cause damage to the surface when removed. Before grouting wall decos, it is advised to protect the surface in the parts near the edge with masking tape. Cement-based, not epoxy-based, grouts must be used. Immediately after grouting, remove any residues with water and a soft cloth, without using abrasive sponges.

Cleaning and Maintenance Wall Decos: For ordinary cleaning, avoid abrasive products that could damage the surface. Cleaning with a soft cloth and neutral PH products is recommended to avoid dulling or scratching.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Rectified Edge
- Soft | Matte | Anti-Slip Finishes
- V2 - Slight Shading Variation
- 6mm | 9mm | 20mm Thicknesses
- Frost Resistance = Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.