



Features	Test Method	Value
Dimensions	ASTM C499	Compliant
Warpage	ASTM C485	± 0.4%
Wedging	ASTM C502	± 0.25%
Water Absorption	ASTM C373	< 0.5%
Breaking Strength	-	> 300 lbf
Frost Resistance	ASTM C650	Resistant
Chemical Resistance	ASTM C1378	Resistant
Stain Resistance	ANSI A137.1	Resistant
Slip Resistance	ANSI A137.1	0.42
Recycled Material	-	≥ 25%
VOC Emissions	-	Zero VOC
Environmental Product Declaration	-	Yes
Declare	-	Red List Free
Health Product Declaration	-	Available
Green Squared Certified	-	Yes
Greenguard Certified	-	Greenguard Gold




This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Natural | Polished Finishes
- 8mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance = Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.