

Features	Test Method	Value	
		Pressed	Rectified
Size Sides	ISO 10545-2	± 0.6% max ± 2.0 mm	± 0.3% max ± 1.0 mm
Thickness		± 5.0% max ± 0.5 mm	
Squareness of Corners		± 0.5% max ± 2.0 mm	± 0.3% max ± 1.5 mm
Straightness of Sides		± 0.5% max ± 1.5 mm	± 0.3% max ± 0.8 mm
Planarity		± 0.5% max ± 2.0 mm	± 0.4% max ± 1.8 mm
Water Absorption		ISO 10545-3	≤ 0.5
Breaking Strength	ISO 10545-4	S ≥ 1300 N	
Bending Resistance	ISO 10545-4	R ≥ 35 N/mm ²	
Abrasion Resistance	ISO 10545-7	5	
Thermal Shock Resistance	ISO 10545-9	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Household	Low Concentration
		A	LA
Stain Resistance	ISO 10545-14	5	
DCOF (WET)	BOT 3000	≥ 0.42	
Recycled Material	-	23%	



This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Natural Finish
- 9mm Thickness
- Rectified | Pressed Edge
- PEI Rating = 5
- V3 - Moderate Variation
- Frost Resistance = Yes



www.genrose.com