

Features	Test Method	Value
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	1600-2400 N
Modulus of Rupture	ISO 10545-4	35-45 N/mm ²
Thermal Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	Household Chemical
		A
Stain Resistance	ISO 10545-14	5
DCOF	ANSI A326.3	0.76
Recycled Material	-	31%



This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 11mm | 12mm Thicknesses
- Rectified Edge
- V1 - Uniform Appearance
- Frost Resistance = Yes

Note: Product is subject to natural shade variation when mixing textures and sizes.



www.genrose.com