

Features	Test Method	Value	
Length and Width	ISO 10545 - 2	±2.00%	
Thickness		±5%	
Straightness of Sides		-0.20%/+0.40%	
Rectangularity		-0.20%/+0.40%	
Surface Flatness		-0.20%/+0.40%	
Surface Quality		Minimum 95% of surface free of visible defects	
Warpage		-0.20%/+0.40%	
Wedging		±0.40%	
Water Absorption		ISO 10545 - 3	18.0% ≤ Eb < 20.0%
Bending Strength	ISO 10545 - 4	6" x 6"	Other Sizes
Breaking Strength		>16 N/mm ²	>13 N/mm ²
		≥ 220 N	≥ 660 N
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	6.0 - 8.0x 10 ⁻⁶ °K ⁻¹	
Thermal Shock Resistance	ISO 10545 - 9	Resistant	
Crazing Resistance	ISO 10545 - 11	Resistant	
Chemical Resistance	ISO 10545 - 13	GA	
Chemical Resistance (Low Concentration)		GLA	
Chemical Resistance (High Concentration)		N/A	
Fire Resistance	-	A1/A1fl	
Recycled Content	-	≤ 15%	
LEED	-	Yes	
VOC Emissions	-	Zero VOC	
Greenguard	-	Greenguard Gold	

This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Ceramic Tile
- Matte | Glossy Finishes
- 5.8mm | 7.5mm
- Pressed Edge
- V1 - Uniform Appearance
- Not Frost Resistant



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.

Features	Test Method	Value		
		Glazed Porcelain	Throughbody Porcelain	Anti-Slip
Length and Width	ISO 10545 - 2	±2.00%		
Thickness		±5%		
Straightness of Sides		±0.40%		
Rectangularity		±0.40%		
Surface Flatness		±0.40%		
Surface Quality		Minimum 95% of surface free of visible defects		
Warpage		±0.40%		
Wedging		±0.25%		
Water Absorption		ISO 10545 - 3	≤0.5%	
Bending Strength	ISO 10545 - 4	≥ 38N/mm ²	60N/mm ²	50 N/mm ²
Breaking Strength		≥ 1430 N	710 N	3500 N
Deep Abrasion Resistance	ISO 10545 - 6	-	≤ 155mm ³	≤ 155mm ³
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	6.0 - 7.0x 10 ⁻⁶ °K ⁻¹		
Thermal Shock Resistance	ISO 10545 - 9	Resistant		
Crazing Resistance	ISO 10545 - 11	Resistant		
Chemical Resistance (Domestic)	ISO 10545 - 13	GA	UA	UA
Chemical Resistance (Low Concentration)		GLA	ULA	ULA
Chemical Resistance (High Concentration)		-	-	-
Fire Resistance	-	A1/A1fl		
Slip Resistance (D.C.O.F.)	ANSI A326.3	Does Not Pass	0.67	0.49
Recycled Content	-	≤ 15% pre-consumer		
LEED	-	Yes		
VOC Emissions	-	Zero VOC		
Greenguard	-	Greenguard Gold		

This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed & Throughbody Porcelain Tile
- Matte | Anti-Slip Finishes
- 3.5mm | 5.8mm | 6mm | 7mm | 7.5mm | 12mm
- Pressed Edge
- V1 - Uniform Appearance (Glazed Only)
- V2 - Slight Shading (Anti-Slip and Unglazed Porcelain Only)
- Frost Resistant



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.