



Features	Test Method	Value	
Thickness	ASTM C-499	max ± 0.030 inch	
Warpage Edge	ASTM C-485	Conforms	
Warpage Diagonal	ASTM C-485	Conforms	
Water Absorption	ASTM C-373	≤ 0.5%	
Breaking Strength	ASTM C-648	³ 510 lb _f average	
Bond Strength	ASTM C-482 ANSI A137.1	Conforms ³ 50 PSI (0.34 MPa)	
Surface Hardness	Mohs Scale	7 Mohs	
Coefficient of Linear Thermal Expansion	ASTM C-372	Conforms	
Thermal Shock Resistance	ASTM C-484	Conforms	
Frost Resistance	ASTM C-1026	Resistant	
Chemical Resistance	ASTM C-650	Conforms	
Stain Resistance	ASTM C-1378	Conforms	
DCOF Dynamic Coefficient of Friction*	ASTM A326.3	Natural	Polished
		≥0.42	Fail
VOC Emissions	-	Zero VOC	
	This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer:

DCOF wet and dry is different on every production lot and can vary. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Through Body Porcelain Tile
- Natural | Polished Finish
- 10mm (Polished) | 10.5mm (Natural) Thicknesses
- Rectified Edge
- PEI Rating = 5
- V2 - Slight Shading Variation
- Frost Resistance = Yes

