





Features	Test Method	Value
Length and Width	ASTM C499	Compliant
Surface Flatness		Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Warpage	ASTM C485	Compliant
Wedging	ASTM C502	Compliant
Water Absorption	ASTM C373	≤ 0.5%
Modulus of Rupture / Bending Strength	ASTM C1500	Compliant
Breaking Strength	ASTM C648	≥ 2200 lbf.
Thermal Shock Resistance	ASTM C484	Resistant
Chemical Resistance (Domestic)	ASTM C650	UA
Chemical Resistance (Low Concentration)		UA
Chemical Resistance (High Concentration)		UA
Slip Resistance (DCOF)	ANSI A326.3	> 0.60
LEED	-	Yes
Environmental Product Declaration	-	Yes
Health Product Declaration	-	Certificate Available
Declare	-	Red List Free
Green Squared	-	Certified
VOC Emissions	-	Zero VOC

This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

- Product Info:**
- Porcelain Paver
 - Rectified Edge
 - Grip Finish
 - V2 - Slight Variation
 - 20mm Thickness
 - Frost Resistant

