


| Features                                                                                                                                                                                                                                                                  | ASTM Test Method                | Value                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-------------------------------------------------------|
| Water Absorption                                                                                                                                                                                                                                                          | C373                            | $\leq 0.1\%$                                          |
| Bond Strength                                                                                                                                                                                                                                                             | C482                            | $\geq 200$ psi                                        |
| Warpage Average                                                                                                                                                                                                                                                           | C485                            | $\leq \pm 0.40\%$                                     |
| Thickness Dimension                                                                                                                                                                                                                                                       | C499                            | $\leq \pm 0.04$ in                                    |
| Facial Dimension                                                                                                                                                                                                                                                          |                                 | $\leq \pm 0.25\%$                                     |
| Wedging Average                                                                                                                                                                                                                                                           | C502                            | $\leq \pm 0.25\%$                                     |
| Breaking Strength                                                                                                                                                                                                                                                         | C648                            | $\geq 400$ lbf                                        |
| Chemical Resistance                                                                                                                                                                                                                                                       | C650                            | Class A                                               |
| Frost Resistance                                                                                                                                                                                                                                                          | C1026                           | Resistant                                             |
| Visible Abrasion Resistance for Glazed Tile                                                                                                                                                                                                                               | C1027                           | Class 4                                               |
| Stain Resistance                                                                                                                                                                                                                                                          | C1378                           | Class A*                                              |
| Hardness (Mohs)                                                                                                                                                                                                                                                           | Scratch Test<br>(Not regulated) | $\geq 7$                                              |
| Coefficient of Friction (Dynamic)                                                                                                                                                                                                                                         | DCOF Acutest (wet)              | Honed Finish $\geq 0.50$<br>Rigato Finish $\geq 0.65$ |
| Recycled Material                                                                                                                                                                                                                                                         | -                               | $\geq 40\%$                                           |
|  <p>This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.</p> |                                 |                                                       |

\*All values given are for matte or honed material. No values are given for polished material. GENROSE does not recommend polished surfaces in areas subject to exposure from grease, oil or water.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

#### Product Info:

- Color Body Porcelain Tile
- Honed | Rigato Finish
- 8mm Thickness
- Rectified | Pressed Edge
- Frost Resistance = Yes
- PEI Rating = 4
- V2 - Slight Shading Variation

MADE IN  
  
U. S. A.



[www.genrose.com](http://www.genrose.com)