

Features	Test Method	Value		
		7 cm ≤ N ≤ 15 cm	N ≥ 15 cm	
Sides	ISO 10545-2	±0.2 mm	±0.6 % (±2.0 mm)	
Thickness	ISO 10545-2	±.5 mm	±5.0 % (±0.5 mm)	
Straightness of Sides	ISO 10545-2	±0.75 mm	± 0,5% (± 1.5 mm)	
Rectangularity	ISO 10545-2	±0.75 mm	± 0,5% (± 2 mm)	
Surface Flatness	ISO 10545-2	±0.75 mm	± 0,5% (± 2,0 mm)	
Water Absorption	ISO 10545-3	≤ 0.1%		
Flexion Resistance	ISO 10545-4	S ≥ 700 N R ≥ 35 N/mm ²		
Impact Resistance	ISO 10545-5	> 0.80		
Coefficient of Linear Thermal - Expansion Linearer	ISO 10545-8	$\mu = 6.7 \times 10^{-6} / C^{\circ}$		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Moisture Expansion (in mm/m)	ISO 10545-10	MAX 0.1 mm / m		
Frost Resistance	ISO 10545-12	Resistant		
Resistance of Chemical Attack	ISO 10545-13	High Concentration	Low Concentration	Domestic Chemicals
		Comply	Comply	B Min
Stain Resistance	ISO 10545-14	Resistant		
Lead and Cadmium Discharge	ISO 10545-15	< Than Instrument Limit		
Skid Resistance	ANSI 137.1-2012 DCOF	> 0.42		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 7mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes

