



| Features | Test Method | Value |
|--|-----------------|---|
| Length And Width | ISO 10545-2 | ±0.2% |
| Thickness | ISO 10545-2 | ±5% |
| Linearity | ISO 10545-2 | ±0.2% |
| Wedging | ISO 10545-2 | ±0.2% |
| Warpage | ISO 10545-2 | ±0.2% |
| Water Absorption | ISO 10545-3 | ≤ 0.06% |
| Bending Strength | ISO 10545-4 | 50 N/mm ² (561 kg/cm ²) |
| Breaking Strength | ISO 10545-4 | 2500 N ≥ 700 N |
| Resistance to Deep Abrasion | ISO 10545-6 | 142 mm ³ |
| Coefficient of Linear Thermal Expansion | ISO 10545-8 | 6.5x10 ⁻⁶ °C ⁻¹ |
| Frost Resistance | ISO 10545-12 | Resistant |
| Resistance of Chemical Attack | ISO 10545-13 | UB Minimum |
| Stain Resistance | ISO 10545-14 | Class 5 |
| Color Resistance to Light | DIN 51094 | No change in brightness or color of samples |
| Slip Resistance | DIN 51130 | It can vary according to the surface finish |
| DCOF | ANSI 137.1:2012 | >0.42 - Matte Structured |
| Recycled Material | - | >40% |
| <p>This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.</p> | | |

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Application:

- All heavy commercial indoor and outdoor areas.

Product Info:

- Through Body Porcelain Tile
- Matte | Polished | Structured Finishes
- 10mm Thickness
- Rectified Edge
- PEI Rating = 5
- V4 - **EXTREME** Variation
- Frost Resistance = Yes

