

Features	Test Method	Value		
Length and Width	ISO 10545-2	± 0.1 %		
Thickness		± 3.0 %		
Straightness of Sides		± 0.1 %		
Rectangularity		± 0.1 %		
Surface Flatness		± 0.1 %		
Water Absorption	ISO 10545-3	E ≤ 0.5 %		
Breaking Strength	ISO 10545-4	> 1300 N		
Modulus of Rupture		> 35 N/mm ²		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Crazing Resistance	ISO 10545-11	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Chemical Resistance	ISO 10545-13	Household/ Swimming Pool Salts	Low Concentration	High Concentration
		GA	GLA	GHA
DCOF (WET)	ANSI A137.1	R10 / B / Class 1		
Stain Resistance	ISO 10545-14	5		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 11mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes

