

Features	Test Method	Value		
Length and Width	ISO 10545-2	± 0,1 %		
Thickness		± 3,0 %		
Straightness of Sides		± 0,1 %		
Rectangularity		± 0,2 %		
Surface Flatness		± 0,2 %		
Water Absorption	ISO 10545-3	≤ 0,1 %		
Breaking Strength	ISO 10545-4	> 2600 N		
Modulus of Rupture		> 53 N/mm <sup>2</sup>		
Abrasion Resistance	ISO 10545-7	5		
Coefficient of Linear Thermal Expansion ( 1/K )	ISO 10545-8	6,7 x 10 <sup>-6</sup>		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Crazing Resistance	ISO 10545-11	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Chemical Resistance	ISO 10545-13	Household/ Swimming Pool Salts	Low Concentration	High Concentration
		GA	GLA	GHA
DCOF (WET)	ANSI B101.3	Matte: R10 /B / Class 2 Anti-Slip: R11 /C / Class 3		
Stain Resistance	ISO 10545-14	5		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte | Anti-Slip Finishes
- 8.8mm | 9.2mm | 10mm | 20mm Thicknesses
- Rectified Edge
- PEI Rating = 5
- V3 - Moderate Variation
- Frost Resistance = Yes

